

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) A data transfer driver for a data storage device including recording media having one or more recording surfaces, one or more data transducer heads positionable relative to the recording surfaces by a head position actuator structure operating within a head position servo loop, the data transfer driver comprising:

- 5 one or more head interfaces, each head interface electrically connected to a transducer head for controlling the transducer head for data read and/or write operations;
- a mode controller electrically connected to each head interface, for controlling the operation of each head interface for selectively reading data from at least one recording surface via at least one transducer head while writing data to at least one recording
- 10 surface via at least one transducer head.

2. (Cancelled)

3. (Original) The data transfer driver of claim 1 wherein the mode controller controls the operation of the head interfaces based on configuration information, wherein the configuration information includes data transfer mode and transducer head selection information.

4. (Cancelled)

5. (Original) The data transfer driver of claim 1 further comprising a control interface connected to the mode controller, the control interface for receiving configuration information wherein the mode controller controls the operation of the head interfaces based on the configuration information.

6. (Original) The data transfer driver of claim 1 wherein each head interface comprises:

a read circuit for controlling the corresponding transducer head to read data from a recording surface, and

5 a write circuit for controlling the corresponding transducer head to write data to a recording surface.

7-11. (Cancelled)

12. (Currently amended) The data transfer driver of claim 1, wherein the data storage device comprises a disk drive and the recording media comprises one or more magnetic data disks, and wherein the mode controller controls the operation of each head interface for selectively reading data from at least one recording surface via at least one transducer head for a distance longer than a servo sector, while writing data to at least one recording surface via at least one transducer head.

5

13-29. (Cancelled)

30. (Currently amended) A disk drive comprising:

recording media having one or more recording surfaces,

one or more data transducer heads,

a head position actuator structure for positioning the heads relative to the

5 recording surfaces, operating within a head position servo loop;

a preamplifier comprising:

one or more head interfaces, each head interface electrically connected to

a transducer head for controlling the transducer head for data read and/or write

operations;

10 a mode controller electrically connected to each head interface and

responsive to the servo controller, for controlling the operation of each head interface

based on configuration information for selectively reading data from at least one

recording surface via at least one transducer head while writing data to at least one

another recording surface via at least one transducer head; and

15 a drive controller configured for controlling the head position actuator structure to

position the heads relative to the recording surfaces, and for providing the configuration

information to the mode controller ~~preamplifier~~ for selectively reading data from at least

one recording surface via at least one transducer head while writing data to at least one

another recording surface via at least one transducer head.

31. (Cancelled)

32. (Original) The disk drive of claim 30 wherein the configuration information includes data transfer mode and transducer head selection information.

33. (Cancelled)

34. (Original) The disk drive of claim 30 wherein the preamplifier further comprises a control interface connected to the mode controller, the control interface for receiving configuration information from the drive controller wherein the mode controller controls the operation of the head interfaces based on the configuration information.

35. (Original) The disk drive of claim 30 wherein each head interface comprises:
a read circuit for controlling the corresponding transducer head to read data from a recording surface, and
a write circuit for controlling the corresponding transducer head to write data to a
5 recording surface.

36. (Currently amended) The disk drive of claim 30, wherein the mode controller further controls the operation of the head interfaces based on the configuration information for writing data to a recording surface via a transducer head while reading data from the recording surface via that same transducer head.

37. (Currently amended) The disk drive of claim 30, wherein the recording media includes one or more data disks having recording surfaces, the disk drive further

including a reference disk having a reference pattern thereon, wherein the ~~transferred~~
reference pattern comprises servo clock information providing transducer head
5 circumferential relative position information, and servo position information providing
transducer head radial relative position information;

wherein the drive controller is further configured for controlling the actuator and
the preamplifier in a servo control loop, for reading the reference pattern from the
reference disk via a transducer head and using the read servo clock and the servo position
10 information to position and maintain one or more other transducer heads on one or more
said data disk recording surfaces while writing final servo patterns onto said one or more
data disk recording surfaces.

38. (Currently amended) The disk drive of claim 37, wherein the drive controller
controls the actuator and the preamplifier for:

reading the reference pattern from the reference disk via a transducer head and
using the read servo clock and the servo position information to position and maintain
5 one or more other transducer heads on one or more said data disk recording surfaces;

while at the same time generating and writing final servo patterns onto said one or
more data disk recording surfaces.

39. (Currently amended) The disk drive of claim 37, wherein the drive controller
further comprises:

a pattern generator for generating the final servo patterns for writing to the
recording surfaces; and

5 a servo controller for controlling the actuator and the preamplifier in a servo
control loop, for reading the reference pattern from the reference disk via a transducer
head and using the read servo clock and the servo position information to position and
maintain one or more other transducer heads on one or more said data disk recording
surfaces while writing the final servo patterns onto said one or more data disk recording
10 surfaces.

40. (Currently amended) A data transfer driver for a data storage device including
recording media having one or more recording surfaces, one or more data transducer
heads positionable relative to the recording surfaces by a head position actuator structure
operating within a head position servo loop, the data transfer driver comprising:

5 one or more head interfaces, each head interface electrically connected to a
transducer head for controlling the transducer head for data read and/or write operations;

a mode controller electrically connected to each head interface, for controlling
~~The data transfer driver of claim 1, wherein the mode controller further controls the~~
operation of each head interface for selectively reading data from at least one recording
10 surface while simultaneously writing data to a plurality of data recording surfaces.

41. (Currently amended) A disk drive comprising:
recording media having one or more recording surfaces,
one or more data transducer heads,
a head position actuator structure for positioning the heads relative to the
5 recording surfaces, operating within a head position servo loop;

a preamplifier comprising:

one or more head interfaces, each head interface electrically connected to
a transducer head for controlling the transducer head for data read and/or write
operations;

10 a mode controller electrically connected to each head interface and
responsive to the servo controller, for controlling the operation of each head interface
based on configuration information ~~The disk drive of claim 30, wherein the mode~~
~~controller further controls the operation of each head interface~~ for selectively reading data
from at least one recording surface via at least one transducer head while simultaneously
15 writing data to a plurality of data recording surfaces via a plurality of transducer heads;
and

a drive controller configured for controlling the head position actuator structure to
position the heads relative to the recording surfaces, and for providing the configuration
information to the mode controller.

42. (Currently amended) A data transfer driver for a data storage device including
recording media having one or more recording surfaces, one or more data transducer
heads positionable relative to the recording surfaces by a head position actuator structure
operating within a head position servo loop, the data transfer driver comprising:

5 one or more head interfaces, each head interface electrically connected to a
transducer head for controlling the transducer head for data read and/or write operations;

a mode controller electrically connected to each head interface, wherein the mode controller controls the operation of the head interfaces based on configuration information including:

10 read mode, wherein the mode controller controls the operation of the head interfaces for selectively reading data via at least one transducer head;

 write mode, wherein the mode controller controls the operation of the head interfaces for selectively writing data via at least one transducer head;

 servowrite mode, wherein the mode controller controls the operation of
15 the head interfaces ~~[[to]]~~ for selectively writing data via a plurality of transducer heads;
 and

 read-while-write (RWW) mode, wherein the mode controller controls the operation of the head interfaces for selectively reading data from at least one recording surface via at least one transducer head while writing data to at least one recording
20 surface via at least one transducer head.

43. (Currently amended) A disk drive comprising:

recording media having one or more recording surfaces,

one or more data transducer heads,

a head position actuator structure for positioning the heads relative to the

5 recording surfaces, operating within a head position servo loop;

a preamplifier comprising:

one or more head interfaces, each head interface electrically connected to a transducer head for controlling the transducer head for data read and/or write operations;

10 a mode controller electrically connected to each head interface and responsive to the servo controller, for controlling the operation of each head interface based on configuration information for selectively reading data from at least one recording surface via at least one transducer head while writing data to at least one recording surface via at least one transducer head; and

15 a drive controller configured for controlling the head position actuator structure to position the heads relative to the recording surfaces, and for providing the configuration information to the preamplifier for selectively reading data from at least one recording surface via at least one transducer head while writing data to at least one recording surface via at least one transducer head,

20 wherein the configuration information includes data transfer mode and transducer head selection information comprising:

 read mode, wherein the mode controller controls the operation of the head interfaces for selectively reading data via at least one transducer head;

 write mode, wherein the mode controller controls the operation of the head
25 interfaces for selectively writing data via at least one transducer head;

 servowrite mode, wherein the mode controller controls the operation of the head interfaces for selectively writing data via a plurality of transducer heads;
and

read-while-write (RWW) mode, wherein the mode controller controls the
30 operation of the head interfaces for selectively reading data from at least one recording
surface via at least one transducer head while writing data to at least one recording
surface via at least one transducer head.

44. (New) A data transfer driver for a data storage device including recording
media having one or more recording surfaces, one or more data transducer heads
positionable relative to the recording surfaces by a head position actuator structure
operating within a head position servo loop, the data transfer driver comprising:
5 one or more head interfaces, each head interface electrically connected to a
transducer head for controlling the transducer head for data read and/or write operations;
a mode controller electrically connected to each head interface, for controlling the
operation of each head interface for selectively reading data from at least one recording
surface via at least one transducer head while writing data to a plurality of recording
10 surfaces via a plurality of transducer heads.

45. (New) A data transfer driver for a data storage device including recording
media having one or more recording surfaces, a plurality of data transducer heads
positionable relative to the recording surfaces by a head position actuator structure
operating within a head position servo loop, the data transfer driver comprising:
5 a plurality of head interfaces, each head interface electrically connected to a
corresponding transducer head for controlling that transducer head for data read and/or
write operations;

a mode controller electrically connected to each head interface, for controlling the operation of each head interface based on configuration information for selectively
10 reading data from at least one recording surface while writing data to a plurality of recording surfaces.

46. (New) The data transfer driver of claim 45 wherein the configuration information includes transducer head selection and data transfer mode information.

47. (New) The data transfer driver of claim 45 wherein each head interface comprises:

a read circuit for controlling the corresponding transducer head to read data from the data disk, and

5 a write circuit for controlling the corresponding transducer head to write data to the data disk.

48. (New) The data transfer driver of claim 45 wherein the mode controller controls the operation of the head interfaces based on the configuration information for writing data to a recording surface via a transducer head while reading data from the recording surface via that same transducer head.

49. (New) The data transfer driver of claim 45 wherein the mode controller controls the operation of the head interfaces based on the configuration information for

writing data to at least one recording surface via at least one transducer head while reading data from at least one recording surface via at least another transducer head.